



REFER DIMENSIONS	TOLERANCE
0~400	± 2
400~800	± 3
800 ↑	± 4



UNIT: □MPa □bar □PSI □Kg/cm ²
MAX WORKING PRESS
SHELL TEST
SEAT TEST
TEST FLUID
WEIGHT: 11.2 kg

FLANGE	PCD	K	FLANGE	PCD	K
PN10	240	M20	JIS 5K	230	M16
PN16	240	M20	JIS 10K	240	M20

FLANGE	PCD	K
ASME B16.5 CLASS 150	241.3	3"/4"-10UNC
BS10 Table E	235	3"/4"-10UNC

MATERIAL TABLE(ASTM)			
BODY	DISC	SEAT	STEM
A536-65-45-12	A536-65-45-12 +NYLON 11	NBR	A182 F6A
	A351 CF8	EPDM	A182 F304
	A351 CF8M	CR	A182 F316
	B148 C95400		

10	LEVER(L7B)	1	ASTM A536-65-45-12
9	BUSH	1	RPTFE+A240 304
8	BUSH	1	ASTM B62
7	O-RING	2	NBR
6	BUSH	1	DELIN
5	PIN	1	ASTM A182 F304
4	SEAT	1	SEE MATERIAL TABLE
3	STEM	1	
2	DISC	1	
1	BODY	1	
ITEM NO.	PART NAME	Q'TY	MATERIAL




VALUE VALVES CO., LTD.

NO.9,CHUNG SHAN RD.,
TU-CHENG INDUSTRIAL DISTRICT,
TAIPEI HSIEN,TAIWAN 236

TEL:+886-2-22698000
FAX:+886-2-22686600
www.valuevalves.com

DESN BY	CHK BY	AUTH BY	ISSUE DATE	2011.06.15
POCKY 2011.06.15		STONE 2011.06.15	MATERIAL	
			SCALE	1/3.5
			UNIT	m/m



VF-733 BUTTERFLY VALVE			
ø150mm LEVER OPERATED			
SIZE	DRAWING NO	REV	
A4	S733015FL02		1